

# elka

14MM CHAMPAGNE OAK

real wood engineered  
flooring



Image represents 1.9m<sup>2</sup>

SPECIES:	<b>European Oak</b>
FINISH:	<b>Brushed, Stained &amp; Oiled</b>
SIZE:	<b>14x190x1820mm (3mm wear layer)</b>

### Colour and grain

**Colour:**  
Heartwood is light brown; some boards may have a pinkish tint or a slight greyish cast. Sapwood is white to cream.

**Grain:**  
Open, with longer rays than red oak. Occasional crotches, swirls and burls. Plain sawn boards have a plumed or flared grain appearance. Softer grain is removed in the brushing process giving a textured surface.

Variations within species and grades:  
Considerable variation among boards in colour and grain texture.

Specification	
Board Dimensions:	14 x 190 x 1820mm (3mm wear layer)
Grade:	Rustic 'B/C/D' (Repaired knots & small repaired splits allowed)
Oak origin:	Mixed EU sources
Profile:	Uniclic Multifit
Bevel:	B2 1.2mm 'long edge only'
Pack Size:	2.0748m <sup>2</sup>
Planks per pack:	6 Layers 1820mm, up to 30% starter boards (600mm +)
Construction:	Oak Wear Layer, Hevia Core, Larch Back
Oil / Lacquer:	UV Cured Oil
Adhesive:	E1
Guarantee:	25 Years Structural
Bathroom:	Must never Install in this area
Conservatory:	Yes
Underfloor heating: Embedded systems only	Yes if installed as a floating floor over underlay incorporating DPM and a maximum contact temp. of 27°C (back of board & sub floor). Electric matting max 150 W/m <sup>2</sup> .
Maintenance:	Elka Oiled maintenance kit
Installation:	Float over underlay, full stick with Elka Trowel Flex

PREFINISHED	All Species	RUSTIC	A – Grade -	B – Grade 30%	C – Grade 30%	D – Grade 40%	For full grading breakdown visit <a href="http://www.elkaflooring.co.uk">www.elkaflooring.co.uk</a>
-------------	-------------	--------	----------------	------------------	------------------	------------------	--

**INSTALLATION IMPLIES ACCEPTANCE**  
NO WARRANTY WILL BE OFFERED FOR APPEARANCE  
RELATED CLAIMS ONCE THE PRODUCT IS INSTALLED

Note: Real wood flooring is a natural product and is subject to natural variations. Any dissatisfaction on grade quality or definition **must** in all cases be notified to Unilin prior to installation.

Imported and distributed by Unilin Distribution  
T: 028 3025 0477

visit our website for full grade specification

[www.elkaflooring.co.uk](http://www.elkaflooring.co.uk)

