

# ELKA®

# WOOD

Image represents 1.8m<sup>2</sup>



## Rural Oak


PACK SIZE:  
**2.812m<sup>2</sup> /pk**  
PIECES /PK:  
**8 planks**

BOARD DIMENSIONS:  
**14 x 189 x 1860mm**  
PRODUCT CODE:  
**ELKA14RURAL**

**14MM**  
**PLANK**

**TONGUE & GROOVE**

SPECIES:	European Oak
FINISH:	Oiled, Smoked, Brushed
SIZE:	1860 x 189 x 14mm / 3mm wear layer



### COLOUR AND GRAIN

This product is created through a fuming (ammonia) process, where the resulting darker colour depends on the natural tannin content of the oak—higher tannin levels produce deeper tones. Because tannin varies between trees, even within the same forest, fumed products naturally display more colour variation than stained finishes, but provide a warmer, more lively character and tone that enhances the natural beauty of the wood. Boards must be well-mixed during installation to achieve a balanced overall look. Natural variation between oak species and grades also contributes to the overall character, with features such as longer rays, occasional crotches, swirls, burls, and the plumed or flared grain patterns typical of plain-sawn boards. You will also find natural saw cuts, as well as large knots, cracks, and other structural features that have been professionally repaired and filled to ensure stability while maintaining the authentic rustic appearance. This inherent diversity in colour, texture, and grain is expected and forms an integral part of the product's aesthetic.

SPECIFICATION	
Board Dimensions:	1860 x 189 x 14mm (3mm wear layer)
Grade:	Rustic 'B/C/D/E' (Smoke, Oil, Sunken Knots, Cracks, Sawn)
Oak origin:	Mixed EU sources
Profile:	T&G
Bevel:	G4 1.2mm 'long & short edge'
Pack Size:	2.8123m <sup>2</sup>
Planks per pack:	8 Layers
Construction:	Oak Wear Layer, Eucalyptus & Poplar multi ply core
Oil / Lacquer:	UV Cured Oil - 2 coats
Adhesive:	E1
Guarantee:	25 Years Structural - 1 Year Oil
Bathroom:	Must <b>never</b> install in this area
Conservatory:	Yes
Underfloor heating:	yes - a maximum contact temp. of 27°C (back of board & sub floor) <i>Refer to floor heating instructions</i>
Sheen:	10% +/-
Maintenance:	Elka Oiled maintenance kit
Installation:	Full stick with Elka Trowel Flex or other PU / MS adhesive

PREFINISHED	RUSTIC	A - Grade	B - Grade 10%	C - Grade 20%	D - Grade 40%	E - Grade 30%	For full grading breakdown visit <a href="http://www.elkaflooring.co.uk">www.elkaflooring.co.uk</a>
-------------	--------	-----------	------------------	------------------	------------------	------------------	--

### INSTALLATION IMPLIES ACCEPTANCE

NO WARRANTY WILL BE OFFERED FOR APPEARANCE  
RELATED CLAIMS ONCE THE PRODUCT IS INSTALLED

**Note: Real wood flooring is a natural product and is subject to natural variations.** Any dissatisfaction on grade quality or definition **must** in all cases be notified to Unilin prior to installation.