

ELKA®

WOOD

Image represents 1.5m²

Clyde Oak

PACK SIZE:
2.075m² /pkBOARD DIMENSIONS:
13 x 120 x 600mmPIECES /PK:
6 planksPRODUCT CODE:
ELKAH20CLYDE13MM
PLANK**UNICLIC**  MULTIFIT
PATENTED TECHNOLOGY

SPECIES: European Oak

FINISH: Brushed, Matt Lacquered

SIZE: 1820 x 190 x 13mm / 2.5mm wear layer



COLOUR AND GRAIN

This product is created through a fuming (ammonia) process, where the resulting darker colour depends on the natural tannin content of the oak—higher tannin levels produce deeper tones. Because tannin varies between trees, even within the same forest, fumed products naturally display more colour variation than stained finishes, but provide a warmer, more characterful appearance that enhances the natural beauty of the wood. Boards must be well-mixed during installation to achieve a balanced overall look. Natural variation between oak species and grades also contributes to the overall character, with features such as longer rays, occasional crotches, swirls, burls, and the plumed or flared grain patterns typical of plain-sawn boards. You will also find natural knots, cracks, and structural features that have been professionally repaired and filled to ensure stability while maintaining the authentic rustic appearance. This inherent diversity in colour and grain texture is expected and forms an integral part of the product's aesthetic.

SPECIFICATION

| | |
|---------------------|--|
| Board Dimensions: | 1820 x 190 x 13mm (2.5mm wear layer) |
| Grade: | Rustic |
| Oak origin: | Mixed EU sources |
| Profile: | Uniclic Multifit |
| Bevel: | G4 1.2mm 4 sides |
| Pack Size: | 2.075m ² |
| Planks per pack: | 6 Layers (up to 30% started boards allowed) |
| Construction: | Oak wear layer, wooden core, spruce backer |
| Oil / Lacquer: | Lacquered - 7 coats |
| Adhesive: | E1 |
| Guarantee: | Structural: 25 years - Finish 5 years |
| Bathroom: | Suitable for use in bathrooms and kitchens |
| Conservatory: | Yes |
| Underfloor heating: | Yes - a maximum contact temp. of 27°C (back of board & sub floor) Refer to floor heating instructions |
| Sheen: | 4% +/- |
| Maintenance: | Elka Lacquered maintenance kit |
| Installation: | Floated or glued |

| | | | | | | | |
|-------------|-------------|--------|----------------|------------------|------------------|------------------|--|
| PREFINISHED | All Species | RUSTIC | A - Grade - | B - Grade 10% | C - Grade 40% | D - Grade 50% | For full grading breakdown visit www.elkaflooring.co.uk |
|-------------|-------------|--------|----------------|------------------|------------------|------------------|--|

INSTALLATION IMPLIES ACCEPTANCE

NO WARRANTY WILL BE OFFERED FOR APPEARANCE
RELATED CLAIMS ONCE THE PRODUCT IS INSTALLED

Note: Real wood flooring is a natural product and is subject to natural variations. Any dissatisfaction on grade quality or definition **must** in all cases be notified to Unilin prior to installation.