

13.5MM CARAMEL OAK

real wood engineered flooring



SPECIES:	European Oak
FINISH:	Oiled, Smoked, Brushed, Sanded Knots
SIZE:	13.5x190x1820mm / 2.5mm wear layer

Colour and grain

Colour:

This product is a fumed product (ammonia treatment). The reaction on the wood which gives the darker colour is dependent on the tannin content of the wood (the more tannin, the darker the result). The tannin content depends on the origin of the oak but even trees from the same forest have a different tannin content. So a fumed product always gives you more colour variation than a stain, but the tone is far warmer, highlights character and helps bring nature into your home. Flooring must be mixed well to achieve a balanced look.

Grain:

The product contains D+ grade with large repaired sunken knots and small unrepaired splits to add character to the product.

Variations within species and grades: Open with longer rays than red oak. Occasional crotches, swirls and burls. Plain sawn boards have a plumed or flared grain appearance.

Specification						
Board Dimensions:	13.5 x 190 x 1820mm (2.5mm wear layer)					
Grade:	Rustic 'B/C/D' (Repaired sunken resin filled knots & small repaired splits allowed)					
Oak origin:	Mixed EU sources					
Profile:	Uniclic Multifit					
Bevel:	4 way bevel					
Pack Size:	2.075m ²					
Planks per pack:	6 Layers 1820mm, up to 30% starter boards (600mm +)					
Construction:	Oak Wear Layer, Hevea Core, Larch Back					
Oil / Lacquer:	UV Cured Oil - 2 coats					
Adhesive:	E1					
Guarantee:	25 Years Structural					
Bathroom:	Must never install in this area					
Conservatory:	Yes					
Underfloor heating:	Yes if installed as a floating floor over underlay incorporating embedded DPM and a maximum contact temp. of 27°C (back of board & sub floor). Electric matting max 150 W/m².					
Maintenance:	Elka Oiled maintenance kit					
Installation:	Float over underlay, full stick with Elka flex					

					1		
PREFINISHED	All Species	RUSTIC	A – Grade	B – Grade	C – Grade	D – Grade	For full grading breakdown
	, Jacoba			20%	30%	50%	
			_	ZU70	3070	5070	visit www.elkaflooring.co.uk

INSTALLATION IMPLIES ACCEPTANCE
NO WARRANTY WILL BE OFFERED FOR APPEARANCE

RELATED CLAIMS ONCE THE PRODUCT IS INSTALLED

Note: Real wood flooring is a natural product and is subject to natural variations. Any dissatisfaction on grade quality or definition **must** in all cases be notified to Unilin prior to installation.

Imported and distributed by Unilin Distribution T: 028 3025 0477









