


# 13.5MM RUSTIC LACQUERED OAK

# real wood engineered flooring



SPECIES:	European Oak
FINISH:	Lacquered
SIZE:	13.5x190x1820mm / 2.5mm wear layer

#### Colour and grain

## Colour:

Heartwood is light brown; some boards may have a pinkish tint or a slight greyish cast. Sapwood is white to cream.

### Grain:

Open, with longer rays than red oak. Occasional crotches, swirls and burls. Plain sawn boards have a plumed or flared grain appearance. Softer grain is removed in the brushing process and giving a textured surface.

Variations within species and grades:

Considerable variation among boards in colour and grain texture.

Specification	
Board Dimensions:	13.5 x 190 x 1820mm (2.5mm wear layer)
Grade:	Rustic 'B/C/D' (Repaired sunken resin filled knots & small repaired splits allowed)
Oak origin:	Mixed EU sources
Profile:	Uniclic Multifit
Bevel:	4 way bevel
Pack Size:	2.075m <sup>2</sup>
Planks per pack:	6 Layers 1820mm, up to 30% starter boards (600mm +)
Construction:	Oak Wear Layer, Hevea Core, Larch Back
Oil / Lacquer:	UV Cured Lacquer
Adhesive:	E1
Guarantee:	25 Years Structural
Bathroom:	Must <b>never</b> install in this area
Conservatory:	Yes
Underfloor heating:	Yes if installed as a floating floor over underlay incorporating embedded DPM and a maximum contact temp. of 27°C (back of board & sub floor). Electric matting max 150 W/m².
Maintenance:	Elka Lacquered maintenance kit
Installation:	Float over underlay, full stick with Elka flex

-   20%   30%   50%	50% visit www.elkaflooring.co.uk
---------------------	----------------------------------

INSTALLATION IMPLIES ACCEPTANCE
NO WARRANTY WILL BE OFFERED FOR APPEARANCE
RELATED CLAIMS ONCE THE PRODUCT IS INSTALLED

Note: Real wood flooring is a natural product and is subject to natural variations. Any dissatisfaction on grade quality or definition **must** in all cases be notified to Unilin prior to installation.

Imported and distributed by Unilin Distribution T: 028 3025 0477

