



127 X 18mm 3 LAYER PLANK RUSTIC OAK FLOORING



Lacquered finish

Appearance General

Colour:

- Heartwood is light brown; some boards may have a pinkish tint or a slight greyish cast. Sapwood is white to cream.

Grain:

- Open, with longer rays than red oak. Occasional crotches, swirls and burls. Plain sawn boards have a plumed or flared grain appearance

Variations Within Species And Grades:

- Considerable variation among boards in colour and grain texture.

Specification:

Brand -	Engineered 127mm Brushed & Lac
Product Dimensions	1200 x 127 x 18
Moisture content:	8% +/-
Grade ?/ Mix	Rustic C/D
Length Spec (from to)	300-1200
Average Length	685
Grade ?/ Mix	BCD MIXED
Finish	Brushed & UV Lacquered
Bevel ?	4 sides bevel
Profile	T&G
Type of Oak	White Oak
Oak Origin	European/American
m ² /box	1.2192
Gross Weight/box	15
Net weight/box #	14.5
boxes/Pallet	48
m ² / Pallet	58.52
PAL Weight	740
Warranty	10y
Certification	no
Satus if not certified	controlled wood
No Lacquer Coats	8
Lacquer Brand	PPG

Workability

Installation:

- Professional & DIY

Sanding:

- Good if the correct sanding sequence is followed

Installing methods allowed:

- Floating over underlay
- Gluing on to Wooden or Concrete Sub-Floor

Features and Advantages:

- Can be laid over under floor heating
- Can be sanded and re-finished
- Made 100% of natural wood
- Ensures excellent thermal and acoustic isolation
- Dimensional stability
- Floor can be laid in all residential areas (except those of high humidity)
- Elka Extras available – underlay, adhesives, finishing profiles & maintenance products. View these at www.elkaflooring.com

Must never do:

- Must not be laid in bathrooms
- Fit where the floor heating exceeds 27c contact temperature

Imported and distributed by Unilin Distribution

Tel: 0844 8118288



REAL WOOD FLOORING

GRADE SPECIFICATION – RUSTIC

UNFINISHED / PREFINISHED					
All Species	RUSTIC	A – Grade -	B – Grade 30%	C – Grade 30%	D – Grade 40%

Grade Specification for Unilin Timber Flooring

Standard grading allowance; maximum of 5% below the actual grade

A Grade

- Best appearance
- Selected for uniformity of light colour
- Slight variation in the natural sapwood colour
- Limited small character marks
- Pin Knots allowed
- Mineral Streaks of less than 3x25mm

B Grade

- Combination of A grade and B grades
- The most standard high grade hardwood flooring sold on the world market
- Excellent appearance
- Variation in the natural sapwood colour
- Limited character marks
- Sound knots of less than 5mm
- Mineral streaks of less than 3 x 100mm
- No stains, open checks or splits.

C Grade

- Variegated appearance
- All colour variations allowed
- Sound knots less than 20mm
- Mineral streaks allowed
- No open splits, holes or voids

D Grade

- Rustic appearance
- All colour variations allowed
- All characteristics of the species allowed
- A serviceable floor after knotholes, wormholes, checks splits and other imperfections are filled and finished.

Please Note: Real wood flooring is a natural product, what is subject to natural variations. The products sold will be a fair representation of the samples as shown.

Any dissatisfaction on grade quality or definition must in all cases be notified to Unilin prior to installation.



TEGA 127 X 18mm 3 LAYER PLANK RUSTIC OAK FLOORING