

14mm Plank Oak B&O

real wood engineered

flooring



Species:	European Oak	
Finish:	Brushed & Oiled	
Size:	145 x 1820 x 14mm / 3mm wear layer	

Colour and grain

Colour:

 Heartwood is light brown; some boards may have a pinkish tint or a slight greyish cast. Sapwood is white to cream.

Grain:

• Open, with longer rays than red oak. Occasional crotches, swirls and burls. Plain sawn boards have a plumed or flared grain appearance

Variations Within Species And Grades:

• Considerable variation among boards in colour and grain texture.

Specification				
Board Dimensions:	145 x 14mm x 1820mm (3mm wear layer)			
Grade:	Rustic 'B/C/D' (Black Repaired Knots + Small Splits)			
Oak origin:	Europe			
Profile:	Uniclic			
Bevel:	B4 1.2mm 'long & short edge'			
Pack Size:	1.5834 M2			
Planks per pack:	Fixed random lengths 1 full pack: 4 x 6ft + 2 x 3ft + 1 x 4ft + 1 x 2ft			
Construction:	Oak Wear Layer, Hevea Core and Spruce Back			
Oil / Lacquer :	UV Oil 2			
Adhesive:	E1			
Guarantee:	15 Years			
Under floor heating:	Yes if installed as a floating floor over underlay incorporating DPM and a maximum contact temperature of 27°C (back of the board and sub floor)			
Maintenance:	Elka Oil Maintenance			
Installation:	Float over underlay, full stick with flex adhesive			

PREFINISHED	RUSTIC	A - Grade	B - Grade	C - Grade	D - Grade	For full grading breakdown - visit
			30%	30%	40%	www.elkaflooring.com

Please Note: Real wood flooring is a natural product, what is subject to natural variations. The products sold will be a fair representation of the samples as shown.

Any dissatisfaction on grade quality or definition must in all cases be notified to Unilin prior to installation.

INSTALLATION IMPLIES ACCEPTANCE NO WARRANTY WILL BE OFFERED FOR APPEARANCE RELATED CLAIMS ONCE THE PRODUCT IS INSTALLED

imported and distributed by Unilin Distribution T: 0844 811 8288 visit our website for full grade specification

www.elkaflooring.com

