

14mm Plank Shaded Walnut

real wood engineered flooring



Walnut Origin:

Profile:

Bevel:

Pack Size:

Planks per pack:

Construction:

Oil / Lacquer :

Adhesive:

Guarantee:

Maintenance:

Installation:

Under floor heating:

145 x 14mm x 1820mm (3mm wear layer)

USA

No

Ε1

Uniclic

1.5834 M2

UV Lacquer

15 Years

Elka Lacquer Maintenance

Rustic 'B/C/D' (Black Repaired Knots + Small Splits)

Walnut Wear Layer, Hevea Core and Spruce Back

Float over underlay, full stick with flex adhesive

6 Layers (Starter boards permitted upto a maximum of 30%)

Yes if installed as a floating floor over underlay incorporating DPM and a maximum contact temperature of 27°C (back of the board and sub floor)

Species:	Walnut USA	Specification
Finish:	sh: Lacquer	
Size:	145 x 1820 x 14mm / 3mm wear layer	Grade:

Colour:

 Heartwood ranges from a deep, rich dark brown to a purplish black. Sapwood is nearly white to tan. Difference between heartwood and sapwood colour is great; some flooring manufacturers steam lumber to bleed the darker heartwood colour into the sapwood

Grain:

Mostly straight and open, but some boards have burled or curly grain.
Arrangements of pores is similar to hickories and persimmon, but pores are smaller in size.

Variations Within Species And Grades:

 Great variety of colour and figure within species, as well as variation in colour among boards, especially in lower grades - Tega is shaded to help blend variation

PREFINISHED	RUSTIC	A - Grade	B - Grade	C - Grade	D - Grade	For full grading breakdown - visit
			30%	30%	40%	www.elkaflooring.com

Please Note: Real wood flooring is a natural product, what is subject to natural variations. The products sold will be a fair representation of the samples as shown. Any dissatisfaction on grade quality or definition must in all cases be notified to Unilin prior to installation. INSTALLATION IMPLIES ACCEPTANCE NO WARRANTY WILL BE OFFERED FOR APPEARANCE RELATED CLAIMS ONCE THE PRODUCT IS INSTALLED

imported and distributed by Unilin Distribution T: 0844 811 8288 visit our website for full grade specification



www.elkaflooring.com