

14mm 3 Strip Oak Lacquer

real wood engineered

flooring



Species:	European Oak
Finish:	UV Lacquer
Size:	13mm x 190mm x 2200 mm

## Colour and grain

Colour:

• Heartwood is light brown; some boards may have a pinkish tint or a slight greyish cast. Sapwood is white to cream.

Grain:

• Open, with longer rays than red oak. Occasional crotches, swirls and burls. Plain sawn boards have a plumed or flared grain appearance

Variations Within Species And Grades:

• Considerable variation among boards in colour and grain texture.

Specification					
Board Dimensions:	13mm x 190mm x 2200 mm (2.5mm wear layer)				
Grade:	Rustic 'B/C/D' (Black Repaired Knots)				
Oak origin:	Europe				
Profile:	Uniclic				
Bevel:	No				
Pack Size:	2.5080 M2				
Planks per pack:	Fixed lengths, 1 full pack = 6 planks				
Construction:	Oak Wear Layer, Hevea Core and Spruce Back				
Oil / Lacquer :	UV Lacquer				
Adhesive:	E1				
Guarantee:	15 Years				
Under floor heating:	Yes if installed as a floating floor over underlay incorporating DPM and a maximum contact temperature of 27°C (back of the board and sub floor)				
Maintenance:	Elka Lacquer Maintenance				
Installation:	Float over underlay, full stick with flex adhesive				

PREFINISHED	RUSTIC	A - Grade	B - Grade	C - Grade	D - Grade	For full grading breakdown - visit
			30%	30%	40%	www.elkaflooring.com

Please Note: Real wood flooring is a natural product, what is subject to natural variations. The products sold will be a fair representation of the samples as shown.

Any dissatisfaction on grade quality or definition must in all cases be notified to Unilin prior to installation.

INSTALLATION IMPLIES ACCEPTANCE NO WARRANTY WILL BE OFFERED FOR APPEARANCE RELATED CLAIMS ONCE THE PRODUCT IS INSTALLED

imported and distributed by Unilin Distribution T: 0844 811 8288 visit our website for full grade specification

www.elkaflooring.com

