

elka

12.5MM ANTIQUE OAK BML

real wood engineered

flooring



Image represents 2.11m²

SPECIES:	European Oak
FINISH:	Stained, Brushed Matt Lacquer
SIZE:	12.5x145x1820mm (2.2mm wear layer)

Colour and grain

Colour:
Heartwood is light brown; some boards may have a pinkish tint or a slight greyish cast. Sapwood is white to cream.

Flooring is stained Antique which evens the colour whilst enhancing the grain and texture.

Grain:
Open, with longer rays than red oak. Occasional crotches, swirls and burls. Plain sawn boards have a plumed or flared grain appearance. Softer grain is removed in the brushing process giving a textured surface.

Variations within species and grades:
Considerable variation among boards in colour and grain texture.

Specification	
Board Dimensions:	12.5mm x 145 x 1820mm (2.2mm wear layer)
Grade:	Rustic 'B/C/D' (Black repaired knots & small repaired splits allowed)
Oak origin:	Mixed EU sources
Profile:	Uniclic
Bevel:	B2 0.75mm 'long edge only'
Pack Size:	1.5834m ²
Planks per pack:	6 Layers 1820mm, up to 30% starter boards (600mm +)
Construction:	Oak Wear Layer, HDF Core & Spruce Back
Oil / Lacquer:	UV Cured Lacquer
Adhesive:	E1
Guarantee:	25 Years Structural - 1 Year Lacquer
Bathroom:	Must never install in this area
Conservatory:	Yes
Underfloor heating:	Yes if installed as a floating floor over underlay incorporating DPM and a maximum contact temp. of 27°C (back of board & sub floor). Electric matting is not suitable or guaranteed.
<i>Embedded systems only</i>	
Maintenance:	Elka Lacquer maintenance kit
Installation:	Float over underlay, full stick with Elka flex adhesive

PREFINISHED	All Species	RUSTIC	A – Grade -	B – Grade 30%	C – Grade 30%	D – Grade 40%	For full grading breakdown visit www.elkaflooring.com
-------------	-------------	--------	----------------	------------------	------------------	------------------	---

INSTALLATION IMPLIES ACCEPTANCE
NO WARRANTY WILL BE OFFERED FOR APPEARANCE RELATED CLAIMS ONCE THE PRODUCT IS INSTALLED

Note: Real wood flooring is a natural product and is subject to natural variations. Any dissatisfaction on grade quality or definition **must** in all cases be notified to Unilin prior to installation.

Imported and distributed by Unilin Distribution
T: 0844 811 8288

visit our website for full grade specification

www.elkaflooring.com

 **UNILIN**
FOR SMART LIVING