

12.5MM DOUBLE WHITE OAK real wood engineered flooring



S

С

С

G

SPECIES: European Oak				Specification							
	•			Board Dimensions:		12.5mm x 145 x 1820mm (2.2mm wear layer)					
FINISH:	Staine	ed, Brusheo	d Matt Lac	quer	Grade:		Rustic	'B/C/D' (Repaired k	nots & small repaired splits allowed)		
SIZE:	12.5x145x1820mm (2.2mm wear layer)				Oak origin:		Mixed EU sources				
					Profile:		Uniclic				
Colour and grain Colour: Flooring is stained with an off white colour enhancing the grain and texture whilst highlighting the sap wood.					Bevel:	Bevel: B2 0.7			75mm 'long edge only'		
					Pack Size:		1.5834m ²				
					Planks per pack:		6 Layers 1820mm, up to 30% starter boards (600mm +)				
					Construction:		Oak Wear Layer, HDF Core & Spruce Back				
Grain: Open, with longer rays than red oak. Occasional crotches, swirls and burls. Plain sawn boards have a plumed or flared grain appearance. Softer grain is removed in the brushing process					Oil / Lacquer:		UV Cured Lacquer				
					Adhesive:		E1				
					Guarantee:		25 Years Structural - 1 Year Lacquer				
giving a te			Bathroom:		Must never Install in this area						
Variations within species and grades:					Conservatory	Conservatory: Yes					
			and grain texture.	Underfloor heating:		Yes if installed as a floating floor over underlay incorporating DPM and a maximum contact temperature of 27°C (back of the board and sub floor)					
					Maintenance:		Elka Lacquer maintenance kit				
			Installation:	Installation:		Float over underlay, full stick with Elka flex adhesive					
PREFINI	SHED	All Species	RUSTIC	A – Grade -	B – Grade 30%	C – G 30%	rade	D – Grade 40%	For full grading breakdown visit www.elkaflooring.com		

INSTALLATION IMPLIES ACCEPTANCE NO WARRANTY WILL BE OFFERED FOR APPEARANCE RELATED CLAIMS ONCE THE PRODUCT IS INSTALLED

Note: Real wood flooring is a natural product and is subject to natural variations. Any dissatisfaction on grade quality or definition **must** in all cases be notified to Unilin prior to installation.

Imported and distributed by Unilin Distribution T: 0844 811 8288

visit our website for full grade specification

www.elkaflooring.com

