



Species:	European Oak
Finish:	Brushed & Oiled
Size:	14 x 190 x 1820mm

Specification	
Board Dimensions:	14 x 190 x 1820mm (3mm wear layer)
Grade:	Rustic 'B/C/D (Repaired Knots upto 80mm in grade D + Small Repaired Splits allowed)
Oak origin:	Mixed EU Sources
Profile:	Uniclic
Bevel:	B4 1.2mm 'long & short edge'
Pack Size:	2.0748 M2
Planks per pack:	6 Layers 1820mm, up to 30% starter boards (600mm +)
Construction:	Oak Wear Layer, Spruce Core, Pine Back
Oil / Lacquer :	UV Cured Oil
Sapwood Allowed:	Yes upto 15%
Adhesive:	E1
Bathroom:	Must never Install in this area
Conservatory:	Yes
Float Install:	Yes - Over Underlay
Guarantee:	25 Years Structural - 1 Year Finish
Under floor heating: Embedded systems	Yes if installed as a floating floor over underlay incorporating DPM and a maximum contact temperature of 27°C (back of the board and sub floor)
Maintenance:	Elka Oil maintenance kit
Installation:	Float over underlay, full stick with Elka flex adhesive

Colour and grain

Colour:

- Heartwood is light brown; some boards may have a pinkish tint or a slight greyish cast. Sapwood is white to cream. Dark stain applied to enhance the aged look of the flooring.

Grain:

- Open, with longer rays than red oak. Occasional crotches, swirls and burls. Plain sawn boards have a plumed or flared grain appearance. Softer grain is removed in the brushing

Variations Within Species And Grades:

- Considerable variation among boards in colour, grain texture and sapwood.

	RUSTIC	A - Grade	B - Grade 30%	C - Grade 30%	D - Grade 40%	For full grading breakdown - visit www.elkaflooring.co.uk
--	--------	-----------	------------------	------------------	------------------	--

INSTALLATION IMPLIES ACCEPTANCE
NO WARRANTY WILL BE OFFERED FOR APPEARANCE
RELATED CLAIMS ONCE THE PRODUCT IS INSTALLED.

Please Note: Real wood flooring is a natural product, what is subject to natural variations. Any dissatisfaction on grade quality or definition must in all cases be notified to Unilin prior to installation.

Imported and distributed by Unilin Distribution

T: 0844 811 8288

visit our website for full grade specification

www.elkaflooring.co.uk