



Image Represents 2 M2

Species:	European Oak
Finish:	Oiled, Smoked, Brushed, Sanded Knots
Size:	190 x 1820 x 14mm / 3mm wear layer

Specification	
Board Dimensions:	190 x 14mm x 1820mm (3mm wear layer)
Grade:	Rustic 'B/C/D +' (Sunken / Sanded Knots & Cracks)
Oak origin:	Europe
Profile:	Uniclic
Bevel:	G4 1.2mm 'long & short edge'
Pack Size:	2.0748 M2
Planks per pack:	6 Layers, up to 30% starter boards (600mm +)
Construction:	Oak Wear Layer, Block Core
Oil (UV Cure):	2 Coats
Adhesive:	E1
Bathroom:	Must never install in this area
Conservatory	Yes
Guarantee:	25 Years Structural - 1 Year Surface Treatment
Under floor heating:	Yes if installed as a floating floor over underlay incorporating DPM and a maximum contact temperature of 27°C (back of the board and sub floor)
Sheen:	6 % +/-
Maintenance:	Elka Oil maintenance kit
Installation:	Float over underlay, full stick with Elka flex adhesive

Colour and grain

This product is a fumed product (ammonia treatment). The reaction on the wood which gives the darker colour is dependent on the tannin content of the wood (**the more tannin the darker the result**) The tannin content depends on the origin of the Oak but even trees from the same forest have a different tannin content.

So a fumed product always gives you more colour variation than a stain but the tone is far warmer, highlights character and helps bring nature in to your home. Flooring must be mixed well to achieve a balanced look.

Character

This product contains D + grade with large repaired sunken and small unrepaired splits to add character to the product

Variations within

Open, with longer rays than red oak. Occasional crotches, swirls and burls. Plain sawn boards have a plumed or flared grain appearance.

PREFINISHED	RUSTIC	A - Grade	B - Grade	C - Grade	D + Grade	For full grading breakdown - visit www.elkaflooring.co.uk
		-	30%	30%	40%	

INSTALLATION IMPLIES ACCEPTANCE
NO WARRANTY WILL BE OFFERED FOR APPEARANCE RELATED CLAIMS ONCE THE PRODUCT IS INSTALLED

Please Note: Real wood flooring is a natural product, what is subject to natural variations. The products sold will be a fair representation of the samples as shown. Any dissatisfaction on grade quality or definition must in all cases be notified to Unilin prior to installation.

imported and distributed by Unilin Distribution
T: 0844 811 8288
visit our website for full grade specification
www.elkaflooring.co.uk