

| SPECIES: | European White Oak        |  |  |  |  |  |
|----------|---------------------------|--|--|--|--|--|
| FINISH:  | Brushed, Oiled & Stained  |  |  |  |  |  |
| SIZE:    | 18 x 150 x Random Lengths |  |  |  |  |  |

## Colour and grain

## Colour:

Heartwood is light brown; some boards may have a pinkish tint or a slight greyish cast. Sapwood is white to cream. Stained to highlight the timber character.

## Grain

Open, with longer rays than red oak. Occasional crotches, swirls and burls. Plain sawn boards have a plumed or flared grain appearance. Softer grain is removed in the brushing process giving a textured surface.

Variations within species and grades:

Considerable variation among boards in colour and grain texture.

| Specification                                   |   |  |  |  |  |
|---|---|--|--|--|--|
| Board Dimensions:                               | 18 x 150 x random lengths 400-1800mm (4mm wear layer)   |  |  |  |  |
| Grade:  | Rustic 'B/C/D' (Black repaired knots & small repaired splits allowed)   |  |  |  |  |
| Oak origin:                                     | Mixed EU sources  |  |  |  |  |
| Profile:  | T&G   |  |  |  |  |
| Bevel:  | B4 1.2mm 'long & short edge'  |  |  |  |  |
| Pack Size:                                      | 1.98m²  |  |  |  |  |
| Planks per pack:                                | 6 Layers 400 - 1800mm   |  |  |  |  |
| Construction:                                   | Oak Wear Layer, Eucalyptus core & back  |  |  |  |  |
| Oil / Lacquer:                                  | UV Cured Lacquer  |  |  |  |  |
| Adhesive:                                       | E1  |  |  |  |  |
| Guarantee:                                      | 25 Years Structural - 1 Year Oil  |  |  |  |  |
| Bathroom:                                       | Must <b>never</b> install in this area  |  |  |  |  |
| Conservatory:                                   | Yes   |  |  |  |  |
| Underfloor heating:<br>Embedded<br>systems only | Yes if installed as a floating floor over underlay incorporating DPM and a maximum contact temp. of 27°C (back of board & sub floor). Electric matting is not suitable or guaranteed. |  |  |  |  |
| Maintenance:                                    | Elka Oiled maintenance kit  |  |  |  |  |
| Installation:                                   | Float over underlay with D3 adhesive, full stick/batten with Elka flex, nail  |  |  |  |  |

|  | PREFINISHED | All Species | RUSTIC | A – Grade<br>- | B – Grade<br>30% | C – Grade<br>30% | D – Grade<br>40% | For full grading breakdown visit www.elkaflooring.com |
|--|-------------|-------------|--------|----------------|------------------|------------------|------------------|---|
|--|-------------|-------------|--------|----------------|------------------|------------------|------------------|---|

INSTALLATION IMPLIES ACCEPTANCE
NO WARRANTY WILL BE OFFERED FOR APPEARANCE
RELATED CLAIMS ONCE THE PRODUCT IS INSTALLED

Note: Real wood flooring is a natural product and is subject to natural variations. Any dissatisfaction on grade quality or definition **must** in all cases be notified to Unilin prior to installation.

Imported and distributed by Unilin Distribution T: 0844 811 8288

visit our website for full grade specification

