



Image represents 2m²

Species:	European Oak
Finish:	Lacquer
Size:	20 x 189 x 1860mm / 4mm wear layer

Colour

Heartwood is light brown; some boards may have a pinkish tint or a slight greyish cast. Sapwood is white to cream.

Grain: Open, with longer rays than red oak. Occasional crotches, swirls and burls. Plain sawn boards have a plumed or flared grain appearance. Softer grain is removed in the brushing process giving a textured surface

Character

Rustic means the full yield of the log is used so variation in colour, grain, repair knots, small unfilled worm holes are all to be expected.

Variations within grades

Open, with longer rays than red oak. Occasional crotches, swirls and burls. Plain sawn boards have a plumed or flared grain appearance.

Specification	
Board Dimensions:	189 x 20mm x 1860mm (4mm wear layer)
Grade:	Rustic 'B/C/D' (Repaired knots & small repaired splits allowed)
Oak origin:	Mixed EU sources
Profile:	T&G
Bevel:	G4 1.2mm 'long & short edge'
Pack Size:	2.11 M2
Planks per pack:	6 Layers, up to 30% starter boards (600mm +)
Construction:	Oak Wear Layer, Eucalyptus & Poplar multi ply core
Lacquer (UV Cure):	7 Coats
Adhesive:	E1
Bathroom:	Must never install in this area
Conservatory:	Yes
Guarantee:	25 Years - 1 Year Surface Treatment
Under floor heating:	Yes if installed as a floating floor over underlay incorporating DPM and a maximum contact temperature of 27°C (back of the board and sub floor) If glued the moisture content of the slab must be <2.5% and the application is full trowel stick with Elka Trowel Adhesive
Sheen:	10% +/-
Maintenance:	Elka Lacquer maintenance kit
Installation:	Float over underlay with D3 adhesive, Nail, Screw or stick with Elka flex or Rigid Adhesive

PREFINISHED	RUSTIC	A - Grade	B - Grade	C - Grade	D - Grade		For full grading breakdown - visit www.elkaflooring.co.uk
		-	30%	40%	40%		

INSTALLATION IMPLIES ACCEPTANCE
NO WARRANTY WILL BE OFFERED FOR APPEARANCE RELATED CLAIMS ONCE THE PRODUCT IS INSTALLED

Please Note: Real wood flooring is a natural product, what is subject to natural variations. The products sold will be a fair representation of the samples as shown.

Any dissatisfaction on grade quality or definition must in all cases be notified to Unilin prior to installation.

imported and distributed by Unilin Distribution

T: 0844 811 8288

visit our website for full grade specification

www.elkaflooring.co.uk