

## Section 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product name:** LUMBERJACK 160

**Product code:** LJACK16010

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** PC1: Adhesives, sealants.

### 1.3. Details of the supplier of the safety data sheet

**Company name:** EVERBUILD BUILDING PRODUCTS LTD

SITE 41, KNOWSTHORPE WAY

CROSS GREEN INDUSTRIAL ESTATE

LEEDS

WEST YORKSHIRE

LS9OSW

ENGLAND

**Tel:** 0044 113 240 3456

**Fax:** 0044 113 240 0024

**Email:** sds@everbuild.co.uk

### 1.4. Emergency telephone number

**Emergency tel:** 0044 113 240 3456 (office hours only)

**Manufacturer:** EVERBUILD BUILDING PRODUCTS LTD

Site 41

Knowsthorpe Way, Cross Green Industrial Estate

Leeds

West Yorkshire

LS9 0SW

United Kingdom

Tel: (0044) 113 240 3456

Fax: (0044) 113 240 0024

Emergency tel: (0044) 113 240 3456

Email: sds@everbuild.co.uk

## Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

**Classification under CHIP:** F: R11; Xi: R36; -: R66; -: R67

**Classification under CLP:** Flam. Liq. 2: H225; Flam. Sol. 1: H228; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH208

# SAFETY DATA SHEET

LUMBERJACK 160

Page: 2

**Most important adverse effects:** Highly flammable. Irritating to eyes. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

## 2.2. Label elements

### Label elements under CLP:

**Hazard statements:** EUH208: Contains 2-butanone oxime. May produce an allergic reaction.  
H225: Highly flammable liquid and vapour.  
H228: Flammable solid.  
H319: Causes serious eye irritation.  
H336: May cause drowsiness or dizziness.

**Signal words:** Danger

**Hazard pictograms:** GHS02: Flame  
GHS07: Exclamation mark



**Precautionary statements:** P102: Keep out of reach of children.  
P271: Use only outdoors or in a well-ventilated area.  
P264: Wash hands and face thoroughly after handling.  
P242: Use only non-sparking tools.  
P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P103: Read label before use.  
P233: Keep container tightly closed.  
P243: Take precautionary measures against static discharge.  
P261: Avoid breathing vapours.  
P280: Wear protective gloves and eye protection.  
P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water/shower.  
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337+313: If eye irritation persists: Get medical advice/attention.  
P312: Call a POISON CENTER or doctor if you feel unwell.  
P370+378: In case of fire: Use powder, water spray or carbon dioxide for extinction.  
P403+233: Store in a well-ventilated place. Keep container tightly closed.  
P405: Store locked up.

### Label elements under CHIP:

**Hazard symbols:** Highly flammable.  
Irritant.

[cont...]

# SAFETY DATA SHEET

LUMBERJACK 160

Page: 3



**Risk phrases:** R11: Highly flammable.  
R36: Irritating to eyes.  
R66: Repeated exposure may cause skin dryness or cracking.  
R67: Vapours may cause drowsiness and dizziness.

**Safety phrases:** S2: Keep out of the reach of children.  
S9: Keep container in a well-ventilated place.  
S16: Keep away from sources of ignition - No smoking.  
S25: Avoid contact with eyes.  
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
S29: Do not empty into drains.  
S43: In case of fire, use alcohol resistant foam, carbon dioxide or water mist.  
S46: If swallowed, seek medical advice immediately and show this container or label.

**Precautionary phrases:** Contains 2-butanone oxime. May produce an allergic reaction.

## 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

ETHYL ACETATE - REACH registered number(s): 01-2119475103-46-XXXX

EINECS	CAS	CHIP Classification	CLP Classification	Percent
205-500-4	141-78-6	F: R11; Xi: R36; -: R66; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	10-30%

ETHANOL

200-578-6	64-17-5	F: R11 Substance with a Community workplace exposure limit.	Flam. Liq. 2: H225	1-10%
-----------	---------	---	--------------------	-------

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

[cont...]

# SAFETY DATA SHEET

LUMBERJACK 160

Page: 4

## 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact. Absorption through the skin may occur causing symptoms similar to those of ingestion.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat. There may be confusion, aggressive behaviour, slurred speech and staggering walk.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

## 4.3. Indication of any immediate medical attention and special treatment needed

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Alcohol resistant foam. Dry chemical powder. Carbon dioxide.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Transfer to a closable, labelled salvage container for disposal by an appropriate method.

### 6.4. Reference to other sections

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space.

[cont...]

# SAFETY DATA SHEET

LUMBERJACK 160

Page: 5

## 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed.

## 7.3. Specific end use(s)

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Hazardous ingredients:**

**ETHYL ACETATE**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	200 ppm	400 ppm	-	-

**ETHANOL**

UK	1920 mg/m3	-	-	-
----	------------	---	---	---

### DNEL/PNEC Values

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Gas/vapour filter, type A: organic vapours (EN141). and must be worn if vapour concentration exceeds WEL

**Hand protection:** Protective gloves. Natural rubber gloves are recommended, neoprene are acceptable.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Paste

**Colour:** Buff

**Odour:** Sweet-smelling

**Evaporation rate:** Moderate

**Solubility in water:** Insoluble

**Viscosity:** Highly viscous

**Boiling point/range°C:** 70-80

**upper:** 13

**Autoflammability°C:** >400

**VOC g/l:** 386.6

**Flammability limits %: lower:** 3

**Flash point°C:** 10

**Relative density:** 1.5-1.6

[cont...]

# SAFETY DATA SHEET

LUMBERJACK 160

Page: 6

## 9.2. Other information

Other information: No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

### 10.4. Conditions to avoid

Conditions to avoid: Heat. Sources of ignition.

### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

#### Hazardous ingredients:

#### ETHYL ACETATE

DERMAL	RBT	LD50	>20000	mg/kg
ORAL	RAT	LD50	6100	mg/kg
ORAL	RBT	LD50	4934	mg/kg
VAPOURS	RAT	4H LC50	29.3	ppmV

#### ETHANOL

IVN	RAT	LD50	1440	mg/kg
ORL	MUS	LD50	3450	mg/kg
ORL	RAT	LD50	7060	mg/kg

#### Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT	Hazardous: calculated

## Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact. Absorption through the skin may occur causing symptoms similar to those of ingestion.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

[cont...]

# SAFETY DATA SHEET

LUMBERJACK 160

Page: 7

**Ingestion:** There may be soreness and redness of the mouth and throat. There may be confusion, aggressive behaviour, slurred speech and staggering walk.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

## Section 12: Ecological information

### 12.1. Toxicity

**Hazardous ingredients:**

#### ETHYL ACETATE

Daphnia magna	48H EC50	3090	mg/l
Pimephales promelas (Fat-head Minnow)	96H LC50	230	mg/l

### 12.2. Persistence and degradability

**Persistence and degradability:** No data available.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** Very low bioaccumulation potential

### 12.4. Mobility in soil

**Mobility:** Volatile.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Waste code number:** 08 04 09

**Disposal of packaging:** Dispose of as normal industrial waste.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN1133

### 14.2. UN proper shipping name

**Shipping name:** ADHESIVES  
(ETHYL ACETATE)

[cont...]

# SAFETY DATA SHEET

LUMBERJACK 160

Page: 8

## 14.3. Transport hazard class(es)

Transport class: 3

## 14.4. Packing group

Packing group: III

## 14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

## 14.6. Special precautions for user

Tunnel code: D/E

Transport category: 3

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** EUH066: Repeated exposure may cause skin dryness or cracking.  
EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.  
H225: Highly flammable liquid and vapour.  
H228: Flammable solid.  
H319: Causes serious eye irritation.  
H336: May cause drowsiness or dizziness.  
R11: Highly flammable.  
R36: Irritating to eyes.  
R66: Repeated exposure may cause skin dryness or cracking.  
R67: Vapours may cause drowsiness and dizziness.

**Legend to abbreviations:** PNEC = predicted no effect level  
DNEL = derived no effect level  
LD50 = median lethal dose  
LC50 = median lethal concentration  
EC50 = median effective concentration  
IC50 = median inhibitory concentration  
dw = dry weight

[cont...]

## SAFETY DATA SHEET

LUMBERJACK 160

Page: 9

bw = body weight

cc = closed cup

oc = open cup

MUS = mouse

GPG = guinea pig

RBT = rabbit

HAM = hamster

HMN = human

MAM = mammal

PGN = pigeon

IVN = intravenous

SCU = subcutaneous

SKN = skin

DRM = dermal

OCC = ocular/corneal

PCP = physico-chemical properties

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.