



SPECIES:	<b>European Oak</b>
FINISH:	<b>Brushed, Stain &amp; Lacquered</b>
SIZE:	<b>13.5x190x1820mm (2.5mm wear layer)</b>

Colour and grain

**Colour:**

Heartwood is light brown; some boards may have a pinkish tint or a slight greyish cast. Sapwood is white to cream.

**Grain:**

Open, with longer rays than red oak. Occasional crotches, swirls and burls. Plain sawn boards have a plumed or flared grain appearance. Softer grain is removed in the brushing process giving a textured surface.

**Variations within species and grades:**

Considerable variation among boards in colour and grain texture.

Specification	
<b>Board Dimensions:</b>	13.5 x 190 x 1820mm (2.5mm wear layer)
<b>Grade:</b>	Rustic 'B/C/D' (Repaired Sunken Resin Filled knots & small repaired splits allowed)
<b>Oak origin:</b>	Mixed EU sources
<b>Profile:</b>	Uniclic
<b>Bevel:</b>	B2 V Groove 'long edge'
<b>Pack Size:</b>	2.0748m <sup>2</sup>
<b>Planks per pack:</b>	6 Layers 1820mm, up to 30% starter boards (600mm +)
<b>Construction:</b>	Oak Wear Layer, Spruce Core, Pine Back
<b>Oil / Lacquer:</b>	UV Cured Lacquer
<b>Adhesive:</b>	E1
<b>Guarantee:</b>	25 Years Structural - 1 Year Finish
<b>Bathroom:</b>	Must never Install in this area
<b>Conservatory:</b>	Yes
<b>Underfloor heating: Embedded systems only</b>	Yes if installed as a floating floor over underlay incorporating Embedded DPM and a maximum contact temp. of 27°C (back of board systems only & sub floor). Electric matting is not suitable or guaranteed
<b>Maintenance:</b>	Elka Maintenance
<b>Installation:</b>	Float over underlay, full stick with Elka flex

PREFINISHED	ALL SPECIES	RUSTIC	A - GRADE	B - GRADE	C - GRADE	D - GRADE	FOR FULL GRADING BREAKDOWN VISIT <a href="http://WWW.ELKAFLOORING.CO.UK">WWW.ELKAFLOORING.CO.UK</a>
			-	20%	30%	50%	

**INSTALLATION IMPLIES ACCEPTANCE**  
NO WARRANTY WILL BE OFFERED FOR APPEARANCE RELATED CLAIMS ONCE THE PRODUCT IS INSTALLED

**Note:** Real wood flooring is a natural product and is subject to natural variations. Any dissatisfaction on grade quality or definition must in all cases be notified to Unilin prior to installation.

Imported and distributed by Unilin Distribution  
T: 0844 811 8288

visit our website for full grade specification

[www.elkaflooring.com](http://www.elkaflooring.com)

