

elka

14MM SUPER RUSTIC

real wood engineered
flooring



Image represents 3m²

SPECIES:	European Oak
FINISH:	Oiled, Brushed, Splits, Sunken Knots
SIZE:	190 x 1820 x 14mm / 3mm wear layer

Colour and grain

Plain sawn boards with open & flared grain & occasional crotches, swirls and burls.

This product is Super Rustic, an extremely characterful timber full of life - large knots and splits have been filled with sunken putty, mineral streaks and colour variation all add to the authenticity of this stunning wood floor.

The oil finish and honey colour is far warmer, highlights character and helps bring nature in to your home.

Flooring must be mixed well during install to achieve a balanced look.

Specification	
Board Dimensions:	190 x 14mm x 1820mm (3mm wear layer)
Grade:	Rustic ++ 'B/C/D' (Sunken Knots and Repaired Splits)
Oak origin:	Europe
Profile:	Uniclic Multifit
Bevel:	G4 1.2mm 'long & short edge'
Pack Size:	2.0748 M ²
Planks per pack:	6 Layers 1820mm, up to 30% starter boards (600mm+)
Construction:	Oak Wear Layer, Hevea Core, Larch Back
Oil :	2 Coats
Adhesive:	E1
Guarantee:	25 Years
Underfloor heating:	Yes if installed as a floating floor over underlay incorporating DPM and a maximum contact temp of 27°C (back of the board and sub floor). Electric matting max 150 W/m ² .
Maintenance:	Elka Oil maintenance kit
Installation:	Float over underlay, full stick with elka flex

PREFINISHED	All Species	RUSTIC	A – Grade -	B – Grade 10%	C – Grade 40%	D – Grade 50%	For full grading breakdown visit www.elkaflooring.co.uk
-------------	-------------	--------	----------------	------------------	------------------	------------------	---

INSTALLATION IMPLIES ACCEPTANCE
NO WARRANTY WILL BE OFFERED FOR APPEARANCE RELATED CLAIMS ONCE THE PRODUCT IS INSTALLED

Note: Real wood flooring is a natural product and is subject to natural variations. Any dissatisfaction on grade quality or definition **must** in all cases be notified to Unilin prior to installation.

Imported and distributed by Unilin Distribution
T: 028 3025 0477

visit our website for full grade specification

www.elkaflooring.co.uk

